


N



Longitudinal joints only

 $\mathcal{O}$ 

 $\tilde{\infty}$ 

Movement rating : Polyurethane = 5/8" Max

Silicone = 11/4" Max

## POST MILES SHEET TOTAL TOTAL PROJECT NO. SHEETS Width (3) the REGISTERED CIVIL ENGINEER Efthymios Delis 1/4" Bevel May 1, 2006 o, C51434 PLANS APPROVAL DATE Exp. 6-30-06 The State of California or its officers or ogents shall not be responsible for the accuracy or completeness of electronic copies of this pic To get to the Caltrans web site, go to: http://www.dot.ca.go.

SAWCUT DETAIL

## NOTES:

- (1) Make smooth cuts from the bottom of seal to  $1\frac{1}{2}$ " clear of top leaving at least one complete cell between the top of the cut and top of the seal. When necessary cut back of seal to clear conduit and round openings.
- (2) Opening in barrier to match width of sawn deck joint.

DIST COUNTY

- Sawcut groove widths shall be as ordered by the Engineer.
- (4) Depth of sawcut: Type A Depth to be shown above. Type B - Depth to be equal to or greater than the depth of seal measured along the contact surface, when compressed to minimum width position (W2) plus dimensions shown above.
- MR (movement rating) as shown on other detail plans.
- Other depths must be approved by the Engineer.

## DIMENSIONS "a" OF JOINT REQUIRED

Movement Rating (MR)	Bridge Type	"a" Dimension		
		Deck Concrete Placed		
		Winter	Fall- Spring	Summer
2"	All except CIP/PS	11/2"	11/4"	3/4"
	CIP/PS	11/4"	1"	5/8"
11/2"	All except CIP/PS	11/4"	1"	5/8"
	CIP/PS	1"	3/4"	5/8"
11/4"	All except CIP/PS	1"	3/4"	5%"
	CIP/PS	3/4"	5/8''	5/8"
5%"	All except CIP/PS	3/4"	3/4"	5/8"
	CIP/PS	5/8"	5/8"	5%"

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

## JOINT SEALS (MAXIMUM MOVEMENT RATING = 2")

NO SCALE

B6-21